



## TECHNICAL DATA SHEET

# KEIM KLINKERENDKAPPE NATUR ELOXIERT

## 1. PRODUCT DESCRIPTION

---

Anodised, powder-coated or painted aluminium clinker end cap.

## 2. FIELD OF APPLICATION

---

For the lateral, limited driving rain tight closure of window sills to ETIC systems, without expansion compensation for subsequent installation of the window sill.

Can only be used in KEIM ETICS in conjunction with a second sealing layer.

## 3. PRODUCT PROPERTIES

---

- ready to use
- easy to use
- easy and fast processing
- driving rain-proof
- fire behaviour: non-flammable

## 4. APPLICATION INSTRUCTIONS

---

### SUBSTRATE PREPARATION:

Remove the protective film in the area where the accessory is placed on the window sill.

per window sill

### APPLICATION:

Push the clinker end cap onto the window sill, starting from the screw-on edge and fitting exactly.  
The end cap must be fitted at right angles to the window sill.

## 5. PACKAGING

---

Product name	Projection	Pieces per unit	Type of container	Length
Klinkerendkappen	50 - 400 mm	2	carton	

Other projections, shaped parts, surfaces, anodising and special colours on request.

## 6. STORAGE

---

max. storage time	Storage conditions
no maximum storage time	dry

### 7. DISPOSAL

---

Waste code: 17 04 02

### 8. SAFETY INSTRUCTIONS

---

No particular indications.

### 9. GENERAL INFORMATION

---

Aluminium window sills, like all weathered surfaces, are subject to varying degrees of dirt and dust deposits depending on the orientation and local conditions. The elements should therefore be cleaned from time to time.

Lukewarm water supplemented with e.g. commercially available surfactants, soft sponge cloths or metal-free brushes are suitable for this purpose.

The stated values and properties are the result of extensive development work and practical experience. Our recommendations for application, whether given verbally or in writing, are intended to provide assistance in the selection of our products and do not establish a contractual relationship. In particular, they do not release the purchaser and processor from the obligation to convince themselves of the suitability of our products for the intended application with due care, which is general practice in trade and crafts. The general rules of construction technology must be observed. We reserve the right to make modifications to improve the product or its application. This edition supersedes all earlier editions.



**KEIMFARBEN GMBH**

Keimstraße 16 / 86420 Diedorf / Tel. +49 821 4802-0 / Fax +49 821 4802-210  
Frederik-Ipsen-Straße 6 / 15926 Luckau / Tel. +49 35456 676-0 / Fax +49 35456 676-38  
[www.keim.com](http://www.keim.com) / [info@keimfarben.de](mailto:info@keimfarben.de)